

SEQENS

ADVANCED SPECIALTIES

KELICO® 3460

High Tech Grease



CONTINUUM OF PROGRESS

KELICO® 3460 is recommended for multi-purpose applications. It can withstand heavy loads with additional additives.

KELICO® 3460 is an overbased calcium sulfonate.

KELICO® 3460 has outstanding performances such as high temperature resistance, mechanical stability, corrosion protection and lubricity.

KELICO® 3460 features:

- Inherent good EP/AW properties
- Good water resistance
- Good anticorrosion protection

Characteristics

PROPERTIES/UNIT	METHODS	TYPICAL VALUE
NLGI Grade	-	3
Texture	Visual	Smooth paste
Color	Visual	Beige-brown
Base oil	-	Mineral Oil ISO 460
Water wash out at 38°C(100.4°F) (h) Dry film thickness = 40 µm	ASTM D 1264	6
Water wash out at 79°C (174.2 °F) (% loss)	ASTM D 1264	10
Emcor Test with distilled water	ISO 11007	2/2
Water Spray off (% Loss)	ISO 11007	11
Dropping point °C (°F)	ASTM D 2265	>260 (>500)

The above values are representative of a current production. They are not specifications.

Inventory status

EINECS Europe	TSCA USA	DSL/NDSL Canada	ENCS Japan	AICS Australia	ECL Korea	PICCS Philippines	NZloC New Zealand	IECSC China	TSCI Taiwan
------------------	-------------	--------------------	---------------	-------------------	--------------	----------------------	----------------------	----------------	----------------

SEQENS

ADVANCED SPECIALTIES

PCAS
21 chemin de la sauvegarde
69134 ECULLY CEDEX
FRANCE

WWW.SEQENS.COM



Performances

PROPERTIES	METHODS	TYPICAL VALUES
4-Balls Weld Load Kg (Lb)	ASTM D 2596	500 (1102)
4-Balls Wear Scar diameter mm (Inch)	ASTM D 2266	0.5 (0.016)

The above values are representative of a current production. They are not specifications.

Packaging: 185 kg net metal drum

Safe Use and Handling: KELICO® 3460 should be stored at room temperature. For specific safe use and handling information, or to obtain KELICO® 3460 Safety Data Sheet, contact your local SEQENS Advanced Specialties representative.

Shelf Life: Shelf life of KELICO® 3460 is 24 months when product is stored in the conditions recommended in the MSDS. After this period, product can be retested for shelf life extension if needed.

SEQENS
ADVANCED SPECIALTIES

PCAS
21 chemin de la sauvegarde
69134 ECULLY CEDEX
FRANCE

WWW.SEQENS.COM

